



Energy Delivered Cleaner.™

Pipeline
Recompression
Pipeline Evacuation
Cross-Compression



Peak Operational Efficiency



Purpose built design. More capacity in a smaller footprint, to put your pipeline back in service sooner.



No third-party trucking. Ease of mobility. Quick response times.



CR offers a near zero methane mission alternative to pipeline evacuation.



Repair, maintain, and test your pipeline without venting or flaring natural gas.



Superior customer experience, safer operations, and a faster more environmentally friendly solution.





high capacity



low noise



modular footprint



GENERAL

- Electric drive compressor
- Natural gas generator
- Compressor footprint (32' L x 8.5' W) ea.
- Generator footprint (26' L x 8.5' W) ea.
- Quiet operation (~70 dBA @ 50 ft)

CODE & STANDARDS

- Electrical Area Classification – NEC Class I, Division 1/2
- ASME Section VIII, Division I
- ASME B31.3
- ISO 8528-5



OVERPRESSURE PROTECTION

- PLC overpressure protection
- PSV protection at each compressor stage
- Adjustable discharge PSV set below pipeline MAOP

FLOW & PRESSURE PERFORMANCE

- 16 MMSCFD maximum flow per unit
- Target suction pressures of 2psi or less
- Discharge pressures up to 1,287psi



832-615-2576

sales@cleanrecompression.com

cleanrecompression.com

Scan QR code to request
a project estimate

