



Energy
Delivered
Cleaner.TM

Recompression
Pipeline Evacuation
Cross-Compression

Peak Operational Efficiency



Purpose built design. More capacity in a smaller footprint, to put your pipeline back in service sooner.



No third-party trucking. Ease of mobility. Quick response times.



CR offers a near zero methane mission alternative to pipeline evacuation.



Repair, maintain, and test your pipeline without venting or flaring natural gas.



Superior customer experience, safer operations, and a faster more environmentally friendly solution.





cleaner/greener



higher capacity



compact footprint



GENERAL

- Electric drive compressor
- Natural gas generator
- Compressor footprint (32' L x 8.5' W) ea.
- Generator footprint (26' L x 8.5' W) ea.
- Quiet operation (~70 dBA @ 50 ft)

CODE & STANDARDS

- API 500, Class 1, Division 2, Electrical Area Classification
- ASME Section VIII, Division I, Pressure Vessels
- ASME B31.3, Process Piping
- ISO 8528-5, Combustion Driven Alternating Current Gensets

SAFETY & OVERPRESSURE PROTECTION

MECHANICAL

- Equipment – full flow pressure safety valve (PSV) at each compressor stage – 1,287 psi
- Discharge PSV – adjusted for pipeline MAOP 1,300 psi

PERFORMANCE

- 16,000,000 SCFD max flow rate ea.
- 5 psi or less target suction pressures
- Contact us for more information



832-615-2576

sales@cleanrecompression.com

cleanrecompression.com

Scan QR code to request
a project estimate

